

General Description:

MAS TILAL is a water-based decorative for interior and exterior paints that renders professional results with simple application convenience. Unlike traditional flux finishes, MAS TILAL does not elaborate intermixing of colours, layering techniques or sophisticated equipment. Simple effortless trowelling is all that required to achieve this very exquisite effect. Due to the natural mineral-blend it provides a Marmorino effect that gives an elegant monochromatic effect and most importantly, it is environment friendly.

Major Uses:

Can be applied on to walls, columns, and other curved surfaces leaving a joint free finish. For external application protection coat of MAS PROTECT is required to ensure a long lasting effect.

Characteristics and Physical Properties:

Viscosity	Paste
Sp. Weight	1.50 kg/li
Yield	750-1000 gms/m ²
Touch Dry	1 – 2 hours
Gloss	Matt
Shelf life	12 months
Application	Trowel
Dilution	Not required
VOC	4.0 g/L

Surface Preparation:

Allow new masonry to dry for 14 days under normal weather conditions before painting. Treat new concrete with a neutralizer and let it dry over night before rinsing with water to remove white crystal (efflorescence) that form on the surface. Let dry for painting. Surface to be painted should be free from oil, grease, dust, dirt, contaminants and all loose grit and mortar.

If repainting, remove all loose paint, scaling, flaking and peeling paint by PAINT REMOVER, rinse and let dry.

Wooden surfaces should be sanded smooth to touch and no slivers on rough edges should remain. Dust-off surface, then wipe with clean rag.

Prime concrete with MAS Masonry Primer (interior), MAS Acrylic Prime White (exterior) and MAS Undercoat Enamel for wooden surfaces.

After primer application apply MAS TILAL by trowel uniformly to fully cover the surfaces. To attain a double colour effects apply another coat of desired tone by trowel and scrape by spatula to enhance the design.

Storage and Handling:

The product must be stored in accordance with national regulations. The product should be kept in a cool and well-ventilated place, protected from heat direct sunlight; containers must be kept tightly closed.

Packing:

MAS TILAL is available in 5KG (4kg base + 1 kg MAS AD pre-weigh bucket and 25 KG (20 kg base + 5kg MAS AD) pre-weigh pail

Physiological Hazards:

MAS TILAL does not contain solvents, nevertheless, good ventilation in working rooms is recommended as well as the use of safety tools and equipment. MAS TILAL is harmful if swallowed. If contact with eyes or skin occurs, wash well with fresh water and seek immediate medical advise.

Precautions:



See Safety Indication Sheet.

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.

MAS PAINTS & CHEMICAL INDUSTRY

P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E

TEL NO: 009716 5311777; FAX: 009716 5311330

Website : <http://www.mas-paints.com>

Email : masuae@emirates.net.ae

