

General Description:

AQUAWOOD STAINS are a blend of concentrated dyestuff and universal stainers dispersed in water to emphasize their colouristic effect. AQUAWOOD STAINS are ready to use materials and comes to many different colours to choose from; they are fully transparent and display the details of woods.

Major Uses:

AQUAWOOD STAINS are used most exclusively to all types of wood, plywood & specially for veneers.

Characteristics and Physical Properties:

| | |
|--------------|--|
| Appearance | Coloured Liquid |
| Sp. Weight | 0.98 kg/liter. |
| Flash Point | 60 ⁰ C |
| Coverage | 7-9 m ² /liter. (Variable depending on the porosity of the timber and the desired colour strength) |
| Storage Life | Unlimited in room temperature |
| Dilution | water |
| VOC | 50 gm./li. |

***Note:** AQUAWOOD STAINS can be mixed with other shades of colour to obtain the desired colour.

Dilution:

AQUAWOOD STAINS are incompatible with solvents therefore it is advisable to dilute the material with potable drinking water. Each AQUAWOOD STAINS are ready for use, and can be mix to others to obtained a different shades of colours.

Method of Application:

Prepare well the wood to be stained, apply wood stains by spraying, dipping, brushing and by scrubbing with cotton waste. Let it dry for 4 - 5 hrs. and proceed to the next stage.

Drying Time:

Veneer and solid woods dries in a couple of hours depending on the temperature condition.

Storage:

Keep material in a cool place below 25⁰C. Keep the container tightly closed.

Physiological Hazards:

AQUAWOOD STAINS do not contain solvents. However, ensure proper ventilation on working areas, wear gloves and safety clothing while application. When contact with eyes, splash with fresh water and seek immediate medical advice.

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.

MAS PAINTS & CHEMICAL INDUSTRY

P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E
TEL NO: 009716 5311777 ; FAX: 009716 5311330

Website : <http://www.mas-paints.com>

Email : masuae@emirates.net.ae

