



CLEAR MATT VARNISH

General Description:

CLEAR MATT VARNISH is a clear gloss varnish based on alkyd resin developed for interior and exterior wooden surfaces. It has a good colour retention, weather resistance, easy to apply and durable finish.

Major Uses:

Ideal for all types of woods, hardwoods, joinery, clipboards. It can also be used on untreated wood and previously treated woods. For exterior, CLEAR MATT VARNISH can only be used with Wood Preservative.

Characteristics and Physical Properties:

Colour	Clear and Tinted
Gloss	Matt
Specific Gravity	0.900
Flash Point	40°C
% Solid Content	45 approx.
Dft.	30 microns
Coverage	14 – 16 m ² / lit.

Application Details:

Method of application	By brush, Spray.
Mixing Ratio	Single Pack
Thinner / Cleaner	Thinner # 155

Surface Preparation:

- Surface must be clean, dry, and free from dirt, oil, grease and other foreign

Drying Time:

Dry touch @ 25°C	5 hrs.
Hard Dry @ 25°C	5 hrs.
Recoating time @ 25°C	8–12 hrs.

Recommended System:

Interior	
Wood Stain	1 coat
CLEAR MATT VARNISH	2 coats.
Exterior	
WOOD PRESERVATIVE	1 coat.
CLEAR MATT VARNISH	1 coat.

Storage and Handling:

CLEAR GLOSS VARNISH should be kept in cool place below 25°C. Shelf life of 12 months minimum in a tightly close container.

Cleaning of Tools:

All tools should be cleaned with Wash Thinner or Thinner # 155 as soon as possible.

Packing:

Available in 4lit (Usg), 20 lit (Pail) and 200lit (Drum)

Physiological Hazards:

CLEAR MATT VARNISH does not contain dangerous solvents, nevertheless, good ventilation in working rooms is recommended as well as the use of safety tools and equipment. CLEAR MATT VARNISH is flammable and

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.

MAS PAINTS & CHEMICAL INDUSTRY

P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E

TEL NO: 009716 5311777; FAX: 009716 5311330

Website : <http://www.mas-paints.com>

Email : masuae@emirates.net.ae



harmful if swallowed. If contact with eyes or skin occurs, wash well with fresh water and seek immediate medical advise..

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.

MAS PAINTS & CHEMICAL INDUSTRY

P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E

TEL NO: 009716 5311777; FAX: 009716 5311330

Website : <http://www.mas-paints.com>

Email : masuae@emirates.net.ae

