

## General Description:

An alkaline medium materials to clean surfaces contaminated with vegetable, animal oils and fats, mineral oils and greases.

## Major Uses:

Suitable for use on wooden, steel, asphalt and concrete. Heavy duty degreasing of engine rooms, food cargo tanks, shipping containers and garbage skips.

## Characteristics and Physical Properties:

Appearance	Colourless liquid
Odour	Ammoniacal
Specific weight	1.0 kg/L
Flash point	Non flammable
Storage life	12 months
coverage	12 m <sup>2</sup> /L

## Method of Application:

Degreaser WB can be applied by swabbing, brushing, mopping or high pressure wash. Though the material is ready to use, it can be diluted with water. Once applied, allow to remain in contact with the surface for approximately 10 -15 minutes then rinse off using a hose or pressure water

## Storage:

Keep material in a cool place below 25<sup>0</sup>C. Keep the container tightly closed. Shelf life of 12 months minimum.

## Cleaning of Tools:

All tools should be cleaned with water as soon as possible.

## Packing:

Available in 4 lit (Plastic Usg.) and 20 lit (Plastic Pail)

## Physiological Hazards:

Degreaser WB contains lye and it is irritant to skin. It is recommended to use rubber gloves and safety tools when application and avoid contact to your eyes. If incident occurs, wash fresh water and seek for medical assistance.

*The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.*

## MAS PAINTS & CHEMICAL INDUSTRY

P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E

TEL NO: 009716 5311777; FAX: 009716 5311330

Website : <http://www.mas-paints.com>

Email : [masuae@emirates.net.ae](mailto:masuae@emirates.net.ae)

