

General Description:

MAS DESERT is decorative trowel-coating with dramatic metallic effect. It provides silky polychromatic finish that enhances the beauty of indoor surfaces.

Advantages:

- For interior use.
- Good adhesion properties.
- Allows the release of any moisture coming up from the ground by capillary action.
- Protect the formation of fungus and algae.
- Ease of application.
- Environment friendly.

Characteristics and Physical Properties:

Colour	As per catalogue
Gloss	Silky
Specific Gravity	1.10-1.20 kg./ lit.
Viscosity	Paste
Coverage	4 – 5 m ² / lit.
Touch Dry	1 – 2 hrs.
Dry to recoat	3 - 4 hrs.
Shelf Life	12 months
Flash Point	65 ⁰ C
Application	By trowel
Thinning / cleaning	Water.

Surface Preparation:

New Substrates:

- New concrete should be cured at least 28 days. Substrate must be free from any form of contaminants.
- Apply 1 coat of MAS Masonry AR Primer as impregnating sealer prior to the application of MAS Masonry Primer.
- Level the surface with MAS PVA Wall filler and sand until smooth.

- Apply 1 – 2 coats of MASCRYL as an intermediate coat.
- Application of 2 coats of MAS DESERT as indicated in application techniques.

Old Concrete (previously painted)

- Remove all blistered, cracked and peeled off paint from the surface.
- Penetrated paint must be cleared and treated with 3% ammonia and water.
- Glossy finish coat must be sanded.
- Apply 1 coat of MAS Masonry AR Primer as impregnating sealer; apply 1 – 2 coats of MASCRYL (desired colour)
- Apply 2 coats of MAS DESERT in any choice of application techniques.

Typical Recommended System:

MAS Masonry AR Primer (optional)	- 1 coat.
MAS Masonry Primer	- 1 coat.
PVA Wall Filler (optional)	- 2 coats.
MASCRYL (Intermediate coat)	- 1 coat.
MAS DESERT	- 2 coats.

Storage:

The product must be stored in accordance with national regulations. The product should be kept in a cool and well ventilated place, protected from heat and direct sunlight. Containers must be kept tightly closed.

Cleaning of Tools:

All tools should be cleaned with water.

Packing:

Available in ½ kg., 1 kg., 5kg. and 25 kg.

Precautions:



See Safety Indication Sheet.

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.

MAS PAINTS & CHEMICAL INDUSTRY

P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E

TEL NO: 009716 5311777; FAX: 009716 5311330

Website : <http://www.mas-paints.com>

Email : masuae@emirates.net.ae

