

General Description:

DURATEX FINE IS high quality fine textured finish based on a pure acrylic latex and high purity silica especially formulated in a tropical climate and contains anti-bacterial and anti-fungal components

Major Uses:

For exterior protection and decoration.

Advantages:

- Alkaline resistant.
- Water vapour permeable.
- Good weather resistance.
- Scrub resistance.
- Good adhesion, abrasion.
- Various texture patterns
- Easy to apply.

Characteristics and Physical Properties:

Colour	As per colour card
Specific gravity	1.670 kg/L
Solid content	76% (w)
Coverage	3 – 4 m ² /L
DFT	200 µm
Touch dry	3 hrs.
Dry to recoat	24 hrs.
Shelf life	12 months
Flash point	>65°C

Surface Preparation:

New Substrates:

- Substrate must be dry and free from any form of contaminants.
- Apply 1 – 2 coats of MAS Acrylic Primer into the substrate. For gypsum and powdery surface apply 1 coat of MAS AR Primer.

- Application of 1 coat of Mascryl # 1000 to reach an optimal hiding prior to the application of DURATEX FINE

Old Concrete (previously painted)

- Remove all blistered, cracked and peeled off paint from the surface.
- Penetrated paint must be cleared and treated with 3% ammonia and water.
- Glossy finish coat must be sanded.
- Apply 1 coat of Masonry AR Primer and application of Acrylic Primer White for an optimal hiding.

Method of Application:

Spetter Coat	
Thinner	Water
Volume of Thinner	Approx. 0 – 5%
Nozzle orifice	4.0 mm
Roller	
Thinner	n/a
Volume of Thinner	n/a

Storage:

The product must be stored in accordance with national regulations. The product should be kept in a cool and well ventilated place, protected from heat and direct sunlight. Contents must be kept tightly closed.

Cleaning of Tools:

All Tools should be cleaned with water.

Packing:

Available in 1Usg. and 5 Usg. Pail

Precautions:



See Safety Indication Sheet.

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.

MAS PAINTS & CHEMICAL INDUSTRY

P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E

TEL NO: 009716 5311777; FAX: 009716 5311330

Website : <http://www.mas-paints.com>

Email : masuae@emirates.net.ae

