

General Description:

A high quality medium textured finish based on a pure acrylic latex and selected aggregates.

Major Uses:

For interior and exterior protection and decoration.

Advantages:

- Alkaline resistant.
- Water vapour permeable.
- Good weather resistance.
- Scrub resistance.
- Good adhesion, abrasion.
- Various texture patterns
- Easy to apply.

Characteristics and Physical Properties:

Appearance	Pasty
Colour	As per colour card
Gloss	Matt
Specific Gravity	1.6Kg. / lit.
Solid content	67% by volume
Coverage	2 - 4 m ² / lit.
Touch Dry	3 hrs
Dry to recoat	24 hrs
Shelf Life	12 months
Flash Point	>65°C
Application	By roller or spray
Thinning / cleaning	Water

Surface Preparation:

New Substrates:

- Substrate must be dry and free from any form of contaminants.
- Apply 1 – 2 coats of MAS Acrylic Primer into the substrate. For gypsum and powdery surface apply 1 coat of MAS Masonry AR Primer.
- Application of Mascryl to reach an optimal hiding prior to the application of DURATEX MEDIUM is an option..

Old Concrete (previously painted)

- Remove all blistered, cracked and peeled off paint from the surface.
- Penetrated paint must be cleared and treated with 3% ammonia and water.
- Glossy finish coat must be sanded.
- Apply 1 coat of Masonry AR Primer and application of Acrylic Primer White for an optimal hiding.

Method of Application:

Roller	
Recommended thinner	Sweet water
Volume of thinner	Approx. 5%
Cleaning	Water
Spetter Coat	
Recommended thinner	Sweet water
Volume of thinner	0 – 5%
Nozzle orifice	4.0 mm

Storage:

The product must be stored in accordance with national regulations. The product should be kept in a cool and well ventilated place, protected from heat and direct sunlight. Contents must be kept tightly closed.

Cleaning of Tools:

All Tools should be cleaned with water.

Packing:

Available in 1Usg. and 5 Usg. Pail

Precautions:



See Safety Indication Sheet.

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.

MAS PAINTS & CHEMICAL INDUSTRY

P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E

TEL NO: 009716 5311777; FAX: 009716 5311330

Website : <http://www.mas-paints.com>

Email : masuae@emirates.net.ae

