

## General Description:

A high quality medium textured finish based on pure acrylic emulsion and selected aggregates. It has very good weather resistance and covers the unevenness in the surface. It contains antifungal and antibacterial additives.

## Major Uses:

For interior and exterior protection and decoration.

## Advantages:

- Alkaline resistant.
- Water vapour permeable.
- Good weather resistance.
- Good adhesion, abrasion.
- Various texture patterns
- Easy to apply.

## Characteristics and Physical Properties:

Colour	As per colour card
Gloss	Gloss/Semigloss/Matt
Specific Gravity	1.25 – 1.4 kg/L
Solid content	55 %
Coverage	1.5 – 2.0 m <sup>2</sup> /L
DFT	250 microns
Touch dry	3 hours
Dry to recoat	6 - 12 hours
Shelf life	12 months
Flash point	>65°C

## Surface Preparation:

### New Substrates:

- Concrete surface must be 28 days old. Apply one coat of Neutralizer prior to the application of the primer.
- Substrate must be dry and free from any form of contaminants. Apply 1 – 2 coats of MAS Acrylic Primer into the substrate.
- For gypsum and powdery surface apply 1 coat of MAS Masonry AR Primer.

- Application of 1 coat of Mascryl # 1000 to reach an optimal hiding prior to the application of DURATEX SAND

### Old Concrete (previously painted)

- Remove all blistered, cracked and peeled off paint from the surface.
- Penetrated paint must be cleared and treated with 3% ammonia and water.
- Glossy finish coat must be sanded.
- Apply 1 coat of Masonry AR Primer and application of Acrylic Primer White for an optimal hiding.

## Method of Application:

Spetter Coat	
Recommended Thinner	-Sweet Water.
Volume of Thinner	-approx.0 – 5%
Nozzle Orifice	- 4.0 mm.
Roller	
Recommended Thinner	-Sweet Water.
Volume of Thinner	-approx. 5%
For cleaning	-Sweet Water.

## Storage:

The product must be stored in accordance with national regulations. The product should be kept in a cool and well-ventilated place, protected from heat and direct sunlight. Contents must be kept tightly closed.

## Cleaning of Tools:

All Tools should be cleaned with water.

## Packing:

Available in 1Usg. and 5 Usg. Pail

## Precautions:



See Safety Indication Sheet.

*The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.*

## MAS PAINTS & CHEMICAL INDUSTRY

P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E

TEL NO: 009716 5311777; FAX: 009716 5311330

Website : <http://www.mas-paints.com>

Email : [masuae@emirates.net.ae](mailto:masuae@emirates.net.ae)



Management System  
ISO 9001:2015  
ISO 14001:2015  
OHSAS 18001:2007

