

TECHNICAL DATA SHEET

GOLD LEAF (SLAG METAL)

<p>Main Characteristics :</p> <p>Gold Leaf thickness of 0.3 m</p> <p>Copper – Zinc</p> <p>Colours : With the variation of the The composition we have</p> <p>The following colours:</p> <ul style="list-style-type: none">• 0 Copper• 1• 2• 2.1/2	<p>Packaging :</p> <ul style="list-style-type: none">• Boxes 10,000 pcs 16x16 cm.• Boxes 25 pcs x 20 (8x8 cm / 14 x 14 cm)• Rolls 156 mm width 50, 75, 100, 400 ml• Mix boxes 0.200, 0.500. l. 2.5 or 5 kg.• Pcs (Abbuerstig) in box 10 kg. <p>Usage:</p> <ul style="list-style-type: none">• Frame Industry. Furniture Industry. Interior Decoration & Etc. <p>Application :</p> <p>The Leaf generally is applied with 2 methods: with Mission or Guazzo. the mission can be flat (3 to 12 hrs) or white water based (2 to 12 hrs) depend from the substrate (Primer) for (Guazzo) the method is the same for the find Gold.</p>	<p>Suggestions:</p> <p>The product is sensitive to humidity tendency to be oxidized, has to be kept into packaging and utilized within minimum time possible after the opening.</p> <p>Security : The product doesn't contain classified damage material not included in EINCS it is metal.</p>
---	---	---

@ Translation of Italian Data Sheet.