

General Description:

LEATHER EFFECT is based on a stained nitrocellulose lacquer with selected pigments. It is designed to provide a natural effect of brown any kind of leather. The effect may vary from small to big crack depending on the density of the applied material.

Application Procedure:

- Surface to be coated must be primed by either Polyurethane / Polyester or NC Sanding Sealer Clear.
- Sanding is required before the application of dyed brown and let it dry for about 5 – 10 minutes.
- Apply 1 – 2 coats of NC Gloss # 031 Clear on MDF or NC Gloss RAL 8002 as intermediate coat and keep it for a few minutes prior to application of NC Cracked Transparent (Leather Tinted).
- Apply 1 – 2 coats of NC Matt clear # 032 or NC Gloss # 031 Clear as protective coat.

Storage:

Store in cool areas below 25°C. Shelf life is 12 months in closed container. Keep container tightly close.

Cleaning of Tools:

All tools should be cleaned with Wash Thinner or NC Thinner # 115 as soon as possible.

Packing:

Available in 1USG and 5USG.

Physiological Hazards:

LEATHER EFFECT FINISH does not contain dangerous solvents, nevertheless, good ventilation in working rooms is recommended as well as the use of safety tools and equipment as a precaution. In case of any contact in your eyes, immediately splash it with fresh water or consult a doctor for assistance.

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.

MAS PAINTS & CHEMICAL INDUSTRY

P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E

TEL NO: 009716 5311777; FAX: 009716 5311330

Website : <http://www.mas-paints.com>

Email : masuae@emirates.net.ae

