

General Description:

MARBLE EFFECT is a combination of polyurethane based on poly – functional saturated polyesters & dyes. It is designed to give the surface a marble – like finish, granite and varieties of marbles. Each design will depend on the method of application and it is suggested to use for interior decorations.

Method of Application:

- The surface to be designed must be undercoated with Polyurethane or Polyester primer.
- Before the application of the intermediate coat, the surface must be smooth and well – prepared to give an even distribution of the diluted dyes.
- Intermediate coats (any choice of colour) will serve as a base coating.

By Spraying :

- The well prepared surface should be sprayed with diluted dyes (any choice of colour) with low air pressure . A second shade of diluted dyes is sprayed over the first with contrasting colour. Amount of thinning gives the intensity level of the desired shade.

Note: To neutralize the design, spray on top a pure acetone.

By sponge:

- With the same process by spraying, it is possible to proceed with the help of sponge, wet by acetone, stamp it on to the surface to obtain a very unique marble design.
- Let it dry for about 30 min. and can be top coated with PU Clear gloss. PU Acrylic finish clear or PU Matt Clear.

Storage:

Store in cool areas below 25^oC. Shelf life is 12 months in closed container. Keep container tightly close.

Cleaning of Tools:

All tools should be cleaned with Wash Thinner or PU Thinner # 105 as soon as possible.

Packing:

Available in 1Usg, and 20 lit Pail.

Physiological Hazards:

MARBLE EFFECT does not contain dangerous solvents, nevertheless, good ventilation in working rooms is recommended as well as the use of safety tools and equipment as a precaution. In case of any contact in your eyes, immediately splash it with fresh water or consult a doctor for assistance.

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.

MAS PAINTS & CHEMICAL INDUSTRY

P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E

TEL NO: 009716 5311777; FAX: 009716 5311330

Website : <http://www.mas-paints.com>

Email : masuae@emirates.net.ae

