



MAS ACRYLIC PRIMER WHITE

General Description:

MAS ACRYLIC PRIMER is an acrylic copolymer undercoat. It has good flow and good penetration in different surfaces.

Major Uses:

For use on exterior and interior surfaces, like plaster, stucco filler, gypsum boards, concrete and asbestos cement sheeting. It is a new generation of coating that gives unmatched and long lasting maintenance free protection for all buildings. It combines both elasticity and breathing properties. While allowing moisture to escape from inside, it prevents penetration of waste and carbon dioxide from outside.

Characteristics and Physical Properties:

Colour	White
% Solid(v)	32
Specific weight	1.35 g/L
Flash point	>65°C
Coverage	8 – 10 m ² /L
Touch dry	60 min.
Recoat	2-3 hours
Overcoating interval	
minimum	12 hrs
maximum	No limitations

Application Method:

Method of Application	By brush, roller or airless spray
Dilution	Max. 5% water
Airless Spray Data	
Pressure	140-190 kg/cm ²
Nozzle tip	0.021” – 0.027”
Spray angle	65 ⁰ - 80 ⁰

Surface Preparation:

- Substrate must be clean and free from any contamination.
- The wood must not contain more than 17% moisture and must be sanded properly.
- After priming, substrate imperfection can be repaired by MAS PVA WALL FILLER to evened up the surface prior to the application of desired topcoats.

Recommended System:

Interior:

MAS AR Primer	- 1 Coat.
MAS Acrylic Primer	- 1 Coat.
PVA Wall Filler	- 2 Coats.
Mastic Royal Silk / Eggshell	- 2 Coats.
Emulsion Topcoat	- 2 Coats.

Exterior:

MAS Acrylic Primer	-1 Coat
Mastex Medium SP	-1 Coat
Durashield/Masdur	-2 Coats

Storage:

The product must be stored in accordance with national regulations. The product should be kept in a cool and well ventilated place, protected from heat and direct sunlight. Contents must be kept tightly closed.

Cleaning of Tools:

All tools should be cleaned with water.

Packing:

Available in 5 USG, 1USG

Physiological Hazards:

● See Safety Indication Sheet.

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.

MAS PAINTS & CHEMICAL INDUSTRY

P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E

TEL NO: 009716 5311777; FAX: 009716 5311330

Website : <http://www.mas-paints.com>

Email : masuae@emirates.net.ae

