



# MAS ACRYLIC STUCCO FILLER

## General Description:

MAS ACRYLIC STUCCO FILLER is a pure acrylic-based putty filler that gives excellent filling properties and smooth finish. It is easy to sand and perfectly formulated for interior and exterior walls.

## Advantages:

- For interior and exterior use.
- Good adhesion properties.
- Good sandability.
- Good drying properties.
- Ease of application.
- Non – toxic and environment friendly.

## Characteristics and Physical Properties:

Colour	White
Gloss	Matt
Specific Gravity	1.75 kg/L
Volume solids	60%
Coverage	1.5 – 3.0 m <sup>2</sup> /L
Touch dry	1 – 2 hrs
Sanding	6 – 8 hrs
Dilution	Not required

## Surface Preparation:

### New Substrates:

- Substrate must be free from any form of contaminants.
- Apply 1 – 2 coats of MAS Masonry AR Primer and MAS Acrylic Primer White into the substrate.
- Application of MAS Acrylic Stucco Filler to smoothen the surface. Application of 1 – 2 coats of Duracoat or Durashield for final top coating.

## Old Concrete (previously painted)

- Remove all blistered, cracked and peeled off paint from the surface.
- Penetrated paint must be cleared and treated with 3% ammonia and water.
- Glossy finish coat must be sanded.
- Apply 1 coat of masonry primer prior to application of ACRYLIC STUCCO FILLER with a rate of 0.5 – 1.0 kg/m<sup>2</sup> depending on the porosity of the surface.

## Application:

Method	Putty knife/trowel
Instruction for use	
Recommended thinner	Sweet water
Volume of thinner	Approx. 0 5 %
Cleaning of tools	Water

## Storage:

The product must be stored in accordance with national regulations. The product should be kept in a cool and well ventilated place, protected from heat and direct sunlight. Contents must be kept tightly closed.

## Cleaning of Tools:

All tools should be cleaned with water.

## Packing:

Available in 1Usg. and 5 Usg. Pail

## Precautions:



See Safety Indication Sheet.

*The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.*

## MAS PAINTS & CHEMICAL INDUSTRY

P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E

TEL NO: 009716 5311777; FAX: 009716 5311330

Website : <http://www.mas-paints.com>

Email : [masuae@emirates.net.ae](mailto:masuae@emirates.net.ae)

