

## General Description:

A high quality structured finish based on a co-polymer and selected natural stone.

## Major Uses:

For interior and exterior protection and decoration.

## Advantages:

- Alkaline resistant.
- Water vapour permeable.
- Good weather resistance.
- Hides small substrate imperfections
- Good adhesion, abrasion.
- Various texture patterns
- Easy to apply.

## Characteristics and Physical Properties:

Color	White and NCS
Gloss	Matt
Specific gravity	1.90 ± 0.10 kg/liter
Solid content (v)	85%
Coverage	0.5 – 1.0 m <sup>2</sup> /liter
Drying time:	
Touch dry	6 h
Recoat	24 h
Shelf life	12 months
Flash point	>65°C
Application	Stainless steel trowel for application and plastic trowel for structuring
Thinning/cleaning	Water

## Surface Preparation:

### New Substrates:

- Substrate must be dry and free from oil and grease.
- All dirt, laitance and other contaminants must be removed.
- Gypsum and powdery surface apply 1 coat of MAS Masonry AR Primer.

- Application of 1 coat of Mas Masonry Primer.
- Lime containing materials should be neutralized.

### Old Concrete (previously painted)

- Remove all blistered, cracked and peeled off paint from the surface.
- Penetrated paint must be cleared and treated with 3% ammonia and water.
- Glossy finish coat must be sanded.
- Apply 1 coat of Masonry AR Primer and application of Masonry Primer White for an optimal hiding.

## Method of Application:

- Apply using the stainless-steel trowel in one thick coat. The grains of material will determine the thickness of the coat.
- As soon as the area of 2-4 sq.m. has been applied, structure the material using the plastic trowel, which has to be roughened before use.
- MAS GRAFFIO can be applied in 3mm and 5mm thickness depending on the requirements.

## Storage:

The product must be stored in accordance with national regulations. The product should be kept in a cool and well-ventilated place, protected from heat and direct sunlight. Contents must be kept tightly closed.

## Cleaning of Tools:

All Tools should be cleaned with water.

## Packing:

Available in 1Usg. and 5 Usg. Pail

## Precautions:



See Safety Indication Sheet.

*The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.*

## MAS PAINTS & CHEMICAL INDUSTRY

P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E

TEL NO: 009716 5311777; FAX: 009716 5311330

Website : <http://www.mas-paints.com>

Email : [masuae@emirates.net.ae](mailto:masuae@emirates.net.ae)

