

General Description:

MAS PERMAGUARD PRIMER is an all acrylic undercoat. It has good flow and good penetration in different surfaces.

Major Uses:

For use on exterior and interior surfaces that requires excellent flexibility and adhesion resistance, like plaster, stucco filler, gypsum boards, concrete and asbestos cement sheeting. It is a new generation of coating that gives unmatched and long lasting maintenance free protection for all buildings. It combines both elasticity and breathing properties. While allowing moisture to escape from inside, it prevents penetration of waste and carbon dioxide from outside.

Characteristics and Physical Properties:

Colour	White
Volume solids	32%
Specific gravity	1.35 kg/L
Thinner	Water
Coverage	8 – 10 m ² /L
Drying time @ 25 ^o C	30 min.
Drying time @ 35 ^o C	20 min.
Recoating	After 8 hours
Application method	Brush, roller or airless spray
Airless Spray Data	
Pressure	1900-2100 psi
Nozzle tip	0.021"-0.027"
Spray angle	65-80 ^o
Dilution rate	5%

Surface Preparation:

- Substrate must be clean and free from any contamination.
- The substrate must be at least 25 days old prior to the application of MAS Masonry AR Primer
- One (1) coat of MAS Permaguard Primer.
- After priming, substrate imperfection can be repaired by MAS ACRYLIC STUCCO FILLER to evened up the surface prior to the application of desired topcoats.

Recommended System:

Interior/ Exterior

MAS Masonry AR Primer	1 coat
MAS Permaguard Primer	1 coat
MAS Acrylic Stucco Filler	1 coat
MAS Permaguard	2 coats

Storage:

The product must be stored in accordance with national regulations. The product should be kept in a cool and well ventilated place, protected from heat and direct sunlight. Contents must be kept tightly closed.

Cleaning of Tools:

All tools should be cleaned with water.

Packing:

Available in 5 USG, 1USG

Physiological Hazards:



See Safety Indication Sheet.

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.

MAS PAINTS & CHEMICAL INDUSTRY

P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E

TEL NO: 009716 5311777; FAX: 009716 5311330

Website : <http://www.mas-paints.com>

Email : masuae@emirates.net.ae

