

## General Description:

MAS STAIN EXTRA is a range of acid dyestuff dispersed in universal solvents to give a high-performance stain with excellent color quality and exceptional coloristic effect. MAS STAIN EXTRA is designed to provide a fast dry and allowable coating time.

## Major Uses:

MAS STAIN EXTRA is recommended to all types of interior wood projects, such as furniture, cabinets, doors and frames, floors and panelling.

## Characteristics and Physical Properties:

Appearance	Coloured Liquid
Specific weight	0.850 kg/L
Viscosity (FC # 4)	11" @ 25 <sup>0</sup> C
Flash point	32 <sup>0</sup> C
Coverage	10 – 12 m <sup>2</sup> /L
Shelf life	2 years

## Available colours:

8028	Medium Oak
8037	Mahogany
8040	Dark Mahogany
8042	Dark Oak
8046	Walnut
8049	Dark Walnut
8076	Pine

## Dilution:

MAS STAIN EXTRA can be diluted both with water and some solvents. White Spirit can be use for a longer workable time. Amount of diluents will depend on the colour strength required. Each stain is ready for use and can be

## Surface Preparation:

Sand the surface with 120-220 grit sand paper. Before staining, ensure that the surface is free from dirt, oil and other contaminants that may cause patches during application.

Existing paints should be remove by Paint Remover and clean with suitable thinner.

## Method of Application:

Mix or shake thoroughly the material to ensure the consistency of the colour and to avoid settlement. Stir occasionally during application. Prepare well the wood to be stained, apply wood stains by spraying, dipping, brushing and by wiping with clean lint-free rag.

Allow to penetrate for 5-10 minutes then wipe excess material in the direction of the grain to obtain homogenous effect.

Let it dry for 1-2 hours and proceed to the next stage.

MAS STAIN EXTRA must be protected with a suitable varnish to maintain the required colour.

## Drying Time:

Veneer and solid woods stained dries in couple of hours depending on the temperature condition.

## Storage:

Keep material in a cool place below 25<sup>0</sup>C. Keep the container tightly closed.

## Physiological Hazards:

MAS STAIN EXTRA contains solvents. Keep away from open flames. Ensure proper ventilation on working areas, wear gloves and safety clothing while application. When contact with eyes, splash with fresh water and seek immediate medical advice.

*The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.*

## MAS PAINTS & CHEMICAL INDUSTRY

P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E

TEL NO: 009716 5311777 ; FAX: 009716 5311330

Website : <http://www.mas-paints.com>

Email : [masuae@emirates.net.ae](mailto:masuae@emirates.net.ae)

