MAS STUCCO

General Description:

MAS STUCCO is water – based putty, based on emulsion resins; special oils and common mineral limes to provide a marble-like finish effect. The glossy appearance and shade of differences obtain gives unique and a great value of decoration for interior.

Advantages and Uses:

- Wall decorative coating for interior plasters and gypsum.
- Water soluble material and environmentally safe.
- Smooth to touch, odourless, non – toxic and extremely pleasing in appearance.

Characteristics and Physical Properties:

Colour	See product catalogues
Appearance	Glossy with matt shade
Density	1.85 kg/li
Volume	54%
Coverage	1.0–1.5 kg/m^2 on plaster
	0.4-0.6 kg/m^2 on gypsum
Average coats	2 or more
Drying time	4 – 6 hours
Recoating	After 6 hours
Dilution	Ready to use
VOC	35 gms/li

Application Procedure:

Prime the substrate with MAS Masonry Primer or Primart on very absorbent and chalky surfaces. Fill any imperfections with MAS PVA Walfiller and seal the surface with Mascryl Matt Emulsion preferably with a color closest to the required Stucco.

Smooth the surface by stainless steel spatula using MAS Stucco to get a uniform finish.

After 6 hours from the last coat, sand with sand paper in order to smooth the surface and take off surface defects.

Apply the last coat of marble stucco by stainless steel spatula thoroughly. To obtain a different effect, choose a different size of spatula, and apply artistically.

After 5 – 10 minutes press the spatula and move it on the surface to obtain more glossy effects.

Storage:

Shelf life 12 months minimum if stored below 25^{0}C.

Cleaning of Tools:

All tools should be cleaned with water as soon as possible.

Packing:

Available in 1 Ltr, 5 Kgs. and 20 Kgs.

Physiological Hazards:

MAS STUCCO does not contain solvents, nevertheless, good ventilation in working rooms is recommended as well as the use of safety tools and equipment. MAS STUCCO is harmful if swallowed. If contact with eyes or skin occurs, wash well with fresh water and seek immediate medical advise.

Precautions:

See Safety Indication Sheet

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.

MAS PAINTS & CHEMICAL INDUSTRY
P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA,
SHARJAH, UNITED ARAB EMIRATES
TEL NO: 009716 5311777; FAX: 009716 5311330
Website : http://www.mas-paints.com
Email : masuae@emirates.net.ae