



MASDUR AS HARDENER

General Description:

MASDUR AS HARDENER contain poly – functional aliphatic isocyanate mix with ester solvent for a non – yellowing for industrial hardener.

Major Uses:

To be mix with polyurethane/acrylic based topcoat that requires non – yellowing finish for industrial application.

Characteristics and Physical Properties:

Appearance	Clear
Solid content	64%
Specific Gravity	1.05 kg/l
Viscosity FC # 4 @20°C	30 sec.
Flash Point	20°C

Storage:

Shelf life of 6 months in close container. Always keep to room temperature and keep away from direct sunlight.

Packing:

Available in 800 ml, 4 litre and 10 lit.

Physiological Hazards:

MASDUR AS HARDENER does not contain dangerous solvents, nevertheless, good ventilation in working rooms is recommended as well as the use of safety tools and equipment. The mixture, in its liquid state is flammable and harmful if swallowed. If contact with eyes occurs, cleanse with fresh water and seek immediate medical advice.

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.

MAS PAINTS & CHEMICAL INDUSTRY

P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E

TEL NO: 009716 5311777; FAX: 009716 5311330

Website : <http://www.mas-paints.com>

Email : masuae@emirates.net.ae



Management System
ISO 9001:2015
ISO 14001:2015
OHSAS 18001:2007
www.tuv.com
ID: 9108655065

