

General Description:

A high quality textured finish based on a acrylic copolymer resin with selected aggregates filler.

Major Uses:

For interior and exterior protection and decoration.

Advantages:

- Alkaline resistant.
- Water vapour permeable.
- Good colour retention properties.
- Good weather resistance.
- Scrub resistance.
- Good adhesion, abrasion.
- Various texture patterns
- Easy to apply.

Characteristics and Physical Properties:

Colour	As per colour card
Gloss	Matt
Specific gravity	1.780 +/- 0.050 kg/L
Solid content (V)	67%
Coverage	2 – 2.5 m ² /L
Relative humidity	70%
Air temperature	5~35°C
Touch dry	3 hours
Dry to recoat	24 hours
Flash point	>65°C
Thinning	Water

Note: The given data must be considered as guidelines. Actual drying time may be shorter or longer depending on the film thickness, temperature and humidity in the working area.

Surface Preparation:

New Substrates:

- Substrate must be 30 days old and must be sound, dry and free from dust, oil, grease, laitance and any form of contaminants.
- Apply 1 – 2 coats of MAS Masonry Primer into the substrate. For gypsum and powdery surface apply 1 coat of MAS Masonry AR Primer and MAS Acrylic Primer White or Mastex Bond Primer.

Old Concrete (previously painted)

- Remove all blistered, cracked and peeled off paint from the surface.
- Penetrated paint must be cleared and treated with 3% ammonia and water.
- Glossy finish coat must be sanded.
- Apply 1 coat of MAS AR Primer and application of Mas Masonry Primer White/Acrylic Primer White for an optimal hiding.

Method of Application:

Instruction for use	
Spetter Coat	
Recommended Thinner	Water
Volume of Thinner	Approx. 0-5%
Nozzle orifice	4.0 mm
Roller	
Recommended Thinner	Water
Volume of Thinner	Approx. 0-5%
For cleaning	Water

Storage:

The product must be stored in accordance with national regulations. The product should be kept in a cool and well ventilated place, protected from heat and direct sunlight. Contents must be kept tightly closed.

Cleaning of Tools:

All Tools should be cleaned with water.

Packing:

Available in 1Usg. and 5 Usg. Pail

Precautions:

Please observe the Safety Indication Form. Mastex Coarse does not contain solvents and hazardous material. Use under well ventilated working place. Do not breathe and inhale mist. If contact with eyes or skin occurs, wash well with fresh water and seek immediate medical advice.

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.

MAS PAINTS & CHEMICAL INDUSTRY

P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E

TEL NO: 009716 5311777; FAX: 009716 5311330

Website : <http://www.mas-paints.com>

Email : masuae@emirates.net.ae

