



NC MATT CLEAR #032

General Description:

NC MATT CLEAR #032 is a lacquer based on nitrocellulose and modified alkyd resins and additives. It is developed to give a great hardness, high elasticity and resistance, excellent covering and perfect transparency.

Major Uses:

Furniture in general, chairs, turned pieces, picture moldings, cabinets, doors etc.

Characteristics and Physical Properties:

Appearance	Liquid, Opaque White
Sp. Weight	0.980 kg.
Flash Point	21°C
Solid by weight	39%
Solid by Volume	30%
Viscosity	20 – 30 poise.
Coverage/ Coat	7 – 8 m ² / lit. Dft.
Gloss	8 – 16%

Method of Application:

By spraying (3- 4 atm) / brushing

- Suitable for wood undercoated with nitro, polyurethane, polyester primer.
- For all prepared woods; 1 – 2 coats of N.C. Matt Clear #032 thinned down with 60 – 100% N.C. Thinner.
- Let it dry for sand with fine sand paper by manual sanding or automatic sanding machine.

- Repeat the top coating process, vertically and horizontally for a good satin finish

Drying Time:

Dust free	10 –15 min.
Set To Touch	20 – 30 min.
Hard Dry	3 hrs.
Pilling Up	24 hrs.

Storage:

Keep material in a cool place below 25°C. Keep the container tightly closed. Shelf life of 12 months minimum.

Cleaning of Tools:

All tools should be cleaned with Wash Thinner or NC Lacquer Thinner as soon as possible.

Packing:

Available in Usg, 5USG (Pail) and 200 ltr (Drum)

Physiological Hazards:

NC MATT CLEAR #032 does not contain dangerous solvents, nevertheless, good ventilation in working rooms is recommended as well as the use of safety tools and equipment. NC MATT CLEAR #032 is flammable and harmful if swallowed. If contact with eyes or skin occurs, wash well with fresh water and seek immediate medical advise.

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.

MAS PAINTS & CHEMICAL INDUSTRY

P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E

TEL NO: 009716 5311777; FAX: 009716 5311330

Website : <http://www.mas-paints.com>

Email : masuae@emirates.net.ae



Management System
ISO 9001:2015
ISO 14001:2015
OHSAS 18001:2007

