

General Description:

Paste like stripping compound based on non – flammable solvents, developed to soften, dissolve and remove old paint layers.

Principal Characteristics:

To remove old alkyd paints and some types of epoxy, emulsion paints and polyurethanes.

Characteristics and Physical Properties:

Color	Clear
Density	approx. 1.2 g / cm ³
Softening time	approx. 15 minutes (faster at higher temperature.)
Shelf life	4 hrs.
Flash Point	20 - 25 ⁰ C

Substrate Condition:

- Remove first loose paint layers by scraping.
- Apply a suitable quantity by soft haired brush.
- Thinner coats must be used on vertical work.

Removal Procedure:

- Brush PAINT REMOVER in a quantity related to the thickness of the paint film that has to be removed.
- Wait between 5 and 10 minutes; remove with a paint scraper or filling knife the softened paint before it dries.
- Repeat this process in case of a very thick (old) paint film until all coats are removed.
- After drying, sand the surface and remove the remainder of the PAINT REMOVER with a brush, thereafter flush with water.

Precautions:

- Do not shake the tin. Puncture the lid before unscrewing, with a small nail wrapped in cloth to release the pressure. Try to avoid contact with skin, the softener in the PAINT REMOVER can burn the skin and is very volatile and dangerous if splashed onto skin, eye etc.
- If material has been in contact with the skin, flush with plenty of water and seek medical advice as soon as possible. This product should be used in well-ventilated areas. Although this product is non-flammable smoking is prohibited during application and for a short time afterwards. (Please refer our material Safety Data Sheet.)

Cleaning of Tools:

Water and N.C. Thinner # 115

Packing:

Available in 1 Usg, 20 lit Pail and 200 lit Drum.

Physiological Hazards:

PAINT REMOVER does not contain dangerous solvents, nevertheless, good ventilation in working rooms is recommended as well as the use of safety tools and equipment. PAINT REMOVER is flammable and harmful if swallowed. If contact with eyes or skin occurs, wash well with fresh water and seek medical advise.

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.

MAS PAINTS & CHEMICAL INDUSTRY

P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E

TEL NO: 009716 5311777; FAX: 009716 5311330

Website : <http://www.mas-paints.com>

Email : masuae@emirates.net.ae

