

General Description:

MAS PALMYRA is a special coating for interiors with aesthetic effect of metal texture. It is realized with new technologies which creates a surfaces characterized by unique feel that gives a new decorative solutions to make your environment an ambiance of sophistication and elegance.

Advantages:

- For interior use.
- Good adhesion properties.
- Ease of application.
- Environment friendly.

Characteristics and Physical Properties:

Colour	As per catalogue
Specific Gravity	1.000+/- 0.005 kg/L
Viscosity	20 poise @ 25 ⁰ C
Coverage	10-13 m ² / Kg.
Shelf Life	12 months
Flash Point	65 ⁰ C
Application	By brush or sponge
Dilution	5% water max. if required
VOC	75 g/L

Surface Preparation:

New Substrates:

- New concrete should be cured at least 28 days.
- Substrate must be free from any form of contaminants.
- Apply 1 coat of MAS Masonry AR Primer as impregnating sealer.
- Level the surface with MAS PVA Wall filler and sand until smooth.
- Apply 1 – 2 coats of MASCRYL as an intermediate coat (optional). Apply 1 coat of MAS PALMYRA in non uniform manner and rotational movements.

Old Concrete (previously painted)

- Remove all blistered, cracked and peeled off paint from the surface.
- Penetrated paint must be cleared and treated with 3% ammonia and water.
- Glossy finish coat must be sanded.
- Apply 1 coat of MAS Masonry AR Primer as impregnating sealer; apply 1 – 2 coats of MASCRYL (desired colour)
- Apply 1 coat of MAS PALMYRA in a specified application technique.

Typical Recommended System:

MAS Masonry AR Primer	- 1 coat.
MAS Masonry Primer (optional)	- 1 coat.
PVA Wall Filler (optional)	- 2 coats.
MASCRYL (Intermediate coat)	- 1 coat.
MAS PALMYRA	- 1 coat.

Storage:

The product must be stored in accordance with national regulations. The product should be kept in a cool and well ventilated place, protected from heat and direct sunlight. Containers must be kept tightly closed.

Cleaning of Tools:

All tools should be cleaned with water.

Packing:

Available in ½ kg., 1 kg., and 5kg.

Precautions:



See Safety Indication Sheet.

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.

MAS PAINTS & CHEMICAL INDUSTRY

P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA,
SHARJAH, UNITED ARAB EMIRATES
TEL NO: 009716 5311777; FAX: 009716 5311330
Website : <http://www.mas-paints.com>
Email : masuae@emirates.net.ae

