

General Description:

Q.D. THINNER 255 is a mixture of aromatic solvents as suitable diluents to all quick drying enamel products. It is manufactured for reducing QD paints with a fast drying effect.

Advantages:

1. Quickly reduces the consistency of the enamel to the required degree.
2. Improves film smoothness of paints when applied either by spray or dipping thus reducing drying times.
3. No "orange peel" developed after the evaporation of Q.D. Thinner, and therefore increases the film hardness along with its gloss.

Characteristics and Physical Properties:

Appearance		Clear
Specific Gravity	ASTM D 1475	0.87 kg/li.
Colour (Saybolt)	ASTM D 1209	+30
Boiling Point	ASTM D 850	56.2°C
Acidity	ASTM D 1613	< 0.03 %
Non-aromatics		40%
Evaporation rate		1.38
Flash point	IP 170	14°C

Storage:

Keep the container tightly closed. Shelf life is unlimited in close container. Keep away from direct sunlight and other sources of heat or ignition; do not smoke in storage areas.

Packing:

Available in USG, 18 lit (Pail) and 200 lit (Drum)

Physiological Hazards:

Q.D. THINNER 255 contains highly flammable solvents. Harmful if inhaled and if absorbed through skin can cause irritation. Always use protective gloves and eye goggles when handling this product. It is highly recommended to provide proper ventilation on working area. Keep out of reach of children. If contact with skin or splash in eyes, wash with fresh water for a couple of minutes while removing contaminated clothing and shoes. If affected by inhalation of vapour, remove to fresh air. If swallowed, call a physician immediately. Do not induce vomiting.

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.

MAS PAINTS & CHEMICAL INDUSTRY

P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E

TEL NO: 009716 5311777; FAX: 009716 5311330

Website : <http://www.mas-paints.com>

Email : masuae@emirates.net.ae



Management System
ISO 9001:2015
ISO 14001:2015
OHSAS 18001:2007
www.tuv.com
ID 910885068

